

PRODUCT NAME: FLOORSCAPE BAMBOO FLOORING

# BPIR DECLARATION

Version: V1 December 2023

---

**DESIGNATED BUILDING PRODUCT:** Class 1

---

## DECLARATION

Floorscape (NZ) Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the [Building \(Building Product Information Requirements\) Regulations 2022](#)

---

## COMPANY DETAILS

<b>Manufacturer Legal and trading name / Address for service</b>	Unilin Group, Ooigemstraat 3 8710, Wielsbeke, West-Flanders, Belgium
<b>Manufacturer Website / Email</b>	<a href="https://unilin.com/en">https://unilin.com/en</a> <a href="mailto:aftersales@unilin.com">aftersales@unilin.com</a>
<b>Importer legal and trading name / Address for service</b>	Floorscape Limited, Unit 3 /19 Triton Drive Auckland 0632
<b>Importer website / email</b>	<a href="https://floorscape.co.nz/">https://floorscape.co.nz/</a> <a href="mailto:sales@floorscape.co.nz">sales@floorscape.co.nz</a>
<b>Importer NZBN</b>	9429031816861
<b>Importer phone number</b>	094760428
<b>Sustainability Information</b>	<a href="https://unilin.com/en/one-home">https://unilin.com/en/one-home</a>
<b>Product Code Identifier</b>	ABW / SENSOL

## DESCRIPTION OF BUILDING PRODUCT / INTENDED USE

Floorscape Bamboo is a floating floor covering which includes 11 coats of hi-tech European coating providing superior scratch resistance and durability over a woven strand Bamboo core. The Uniclic joining system allows for tight joints and ease of installation.

The full range of Floorscape Bamboo product can be found at [www.floorscape.co.nz/our-brands/arc-bamboo](http://www.floorscape.co.nz/our-brands/arc-bamboo)

## RELEVANT NEW ZEALAND BUILDING CODE CLAUSES

CLAUSE	EVIDENCE
<b>B2 Durability — B2.3.1 (c)</b>	Floorscape Bamboo has durability of over 20 years where installation, and care and maintenance instructions are followed. Durability is proven through achieving the requirement of standard EN16511 : Specifies the characteristics of semi-rigid multilayer modular floor covering with a wear-resistant and decorative surface layer supplied in panels (AC4 rating)
<b>C3 Fire affecting areas beyond the fire source — C3.4 (b)</b>	Floorscape Bamboo meets the requirements of C3 through standard ASISO 9239.1-2003 Reaction to Fire Tests for Floorings (AWTA test certification)
<b>D1 Access Routes — D1.3.3 (d)</b>	Floorscape Bamboo has slip resistant ratings per standard AS4586:2013 Wet Pendulum Slip Resistance Test (ATTAR test certification).
<b>E3 Internal moisture — E3.3.3, E3.3.5, E3.3.6</b>	As an 'Alternative Solution', Floorscape Bamboo is proven to be impervious and easy-to-clean through ISO4760 Topical Moisture Resistance – assembled joint (NZWTA test certification), and through the following of care and maintenance instructions. See further detail here:  <a href="#">E3 Documentation - Floorscape</a>
<b>F2 Hazardous building materials — F2.3.1</b>	Floorscape Bamboo meets the requirements of standard ASTM D5116 Emission Standard: Guide for small-scale environmental chamber determinations of organic emissions from indoor material/products (CETEC test certification)
<b>G3 Food preparation and prevention of contamination — G3.3.2 (b)</b>	Floorscape Bamboo meets this requirement where care and maintenance instructions are followed.
<b>G6 Airborne and impact sound — G6.3.1, G6.3.2</b>	Floorscape Bamboo has acoustic certification for standard ISO140-7 : Sound Transmission and Insulation standard (SLR test certification)

Supporting documentation for the above can be found at [www.floorscape.co.nz/technical-hub](http://www.floorscape.co.nz/technical-hub)

## SCOPE OF USE AND LIMITATIONS

SCOPE	LIMITATION
Can be installed in all general interior areas of a building, including high traffic areas	<ul style="list-style-type: none"> <li>- Remove all existing carpet or soft flooring and underlays</li> <li>- Is not recommended inside showers or saunas</li> <li>- Must be installed over recommended underlay</li> <li>- Not suitable for exterior use</li> <li>- The floor must be able to move freely</li> </ul>

	<ul style="list-style-type: none"> <li>- All subfloors need to be sound and structurally stable enough to be installed atop. Any loose parts of the subfloor or hard flooring need to be secured, repaired, or removed and replaced. Subfloor must be flat with no unevenness greater than 2mm over the length of 1 metre in any direction. Clean and free of old adhesives, building rubble etc prior to installation. Concrete subfloors must test below 80%RH. Timber subfloors must test below 14%MC.</li> <li>- See Installation &amp; Care and Maintenance Instructions for further information <a href="http://www.floorscape.co.nz/technical-hub">www.floorscape.co.nz/technical-hub</a></li> </ul>
Underfloor Heating systems	- Not suitable for Underfloor Heating Systems
Suitable for Wet Areas (E.g., Bathroom, Toilet, Laundry, Kitchen)	<ul style="list-style-type: none"> <li>- Suitable for use in wet areas if specific installation requirements are met as detailed here: <a href="http://www.floorscape.co.nz/installation/bamboo-installation">www.floorscape.co.nz/installation/bamboo-installation</a></li> <li>- Not suitable for bathrooms</li> </ul>

Supporting documentation including Installation instructions, Care and Maintenance instructions, and warranty information can be found at [www.floorscape.co.nz/technical-hub](http://www.floorscape.co.nz/technical-hub)

## RESPONSIBLE PERSON

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Floorscape Bamboo is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of Floorscape Limited:



Mike Caird  
 GENERAL MANAGER SALES & MARKETING  
 23 November 2023