

PRODUCT NAME: FLOORSCAPE CORK FLOORING

# BPIR DECLARATION

Version: V1 December 2023

**DESIGNATED BUILDING PRODUCT:** Class 1

## DECLARATION

Floorscape (NZ) Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the [Building \(Building Product Information Requirements\) Regulations 2022](#)

## COMPANY DETAILS

<b>Manufacturer Legal and trading name / Address for service</b>	Unilin Group, Ooigemstraat 3 8710, Wielsbeke, West-Flanders, Belgium
<b>Manufacturer Website / Email</b>	<a href="https://unilin.com/en">https://unilin.com/en</a> <a href="mailto:aftersales@unilin.com">aftersales@unilin.com</a>
<b>Importer legal and trading name / Address for service</b>	Floorscape Limited, Unit 3 /19 Triton Drive Auckland 0632
<b>Importer website / email</b>	<a href="https://floorscape.co.nz/">https://floorscape.co.nz/</a> <a href="mailto:sales@floorscape.co.nz">sales@floorscape.co.nz</a>
<b>Importer NZBN</b>	9429031816861
<b>Importer phone number</b>	094760428
<b>Sustainability Information</b>	<a href="https://unilin.com/en/one-home">https://unilin.com/en/one-home</a>
<b>Product Code Identifier</b>	RC

## DESCRIPTION OF BUILDING PRODUCT / INTENDED USE

Floorscape Cork is a floor covering that is made-up of a high-density natural cork surface coated with 5 layers of UV cured lacquer, over a moisture resistant, high-density fibreboard. Floorscape Cork is naturally hypoallergenic, and with the patented Mibroban® treatment, the growth of stain & odour causing bacteria, mold and mildew is inhibited. Floorscape Cork includes our innovative Uniclic® joining system to ensure a tight joint and ease of installation

## RELEVANT NEW ZEALAND BUILDING CODE CLAUSES

CLAUSE	EVIDENCE
<b>B2 Durability — B2.3.1 (c)</b>	Floorscape Cork has durability of over 20 years where installation, and care and maintenance instructions are followed. Floorscape Cork meets the requirements of B2 through standard EN 14085 : Resilient floor coverings –

	Specification for floor panels for loose laying (AC4 Durability rating per TDS Document)
<b>C3 Fire affecting areas beyond the fire source — C3.4 (b)</b>	Floorscape Cork meets the requirements of C3 through standard ISO9239-1 : Reaction to Fire Tests for Floorings. (TDS Document)
<b>D1 Access Routes — D1.3.3 (d)</b>	Floorscape Cork has slip resistant ratings per standard AS4586:2013 Wet Pendulum Slip Resistance Test (TDS Document)
<b>E3 Internal moisture — E3.3.3, E3.3.5, E3.3.6</b>	As an 'Alternative Solution', Floorscape Engineered Timber is proven to be impervious and easy-to-clean through ISO4760 Topical Moisture Resistance – assembled joint (NZWTA test certification), and through the following of care and maintenance instructions.
<b>F2 Hazardous building materials — F2.3.1</b>	Floorscape Cork meets the requirements of standard ASTM D5116 : Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products (TDS Document)
<b>G3 Food preparation and prevention of contamination — G3.3.2 (b)</b>	Floorscape Cork meets this requirement where care and maintenance instructions are followed.
<b>G6 Airborne and impact sound — G6.3.1, G6.3.2</b>	Floorscape Cork Timber has acoustic certification for standard ISO140-7 : Sound Transmission and Insulation standard (SLR test certification)

Supporting documentation for the above can be found at [www.floorscape.co.nz/technical-hub](http://www.floorscape.co.nz/technical-hub)

## SCOPE OF USE AND LIMITATIONS

SCOPE	LIMITATION
Can be installed in all general interior areas of a building, including high traffic areas	<ul style="list-style-type: none"> <li>- Remove all existing carpet or soft flooring and underlays</li> <li>- Is not recommended inside showers or saunas</li> <li>- Must be installed over recommended underlay</li> <li>- Not suitable for exterior use</li> <li>- The floor must be able to move freely</li> <li>- All subfloors need to be sound and structurally stable enough to be installed atop. Any loose parts of the subfloor or hard flooring need to be secured, repaired, or removed and replaced. Subfloor must be flat with no unevenness greater than 2mm over the length of 1 metre in any direction. Clean and free of old adhesives, building rubble etc prior to installation. Concrete subfloors must test below 80%RH. Timber subfloors must test below 14%MC.</li> <li>- See Installation &amp; Care and Maintenance Instructions for further information <a href="http://www.floorscape.co.nz/technical-hub">www.floorscape.co.nz/technical-hub</a></li> </ul>

Underfloor Heating systems	Not suitable for Underfloor Heating Systems
Suitable for Wet Areas (E.g., Bathroom, Toilet, Laundry, Kitchen)	- See Installation Instructions for detail around perimeter finish <a href="http://www.floorscape.co.nz/installation/timber-installation">www.floorscape.co.nz/installation/timber-installation</a> - Only Quick-Step Faro and Amato styles are suitable for bathrooms

Supporting documentation including Installation instructions, Care and Maintenance instructions, and warranty information can be found at [www.floorscape.co.nz/technical-hub](http://www.floorscape.co.nz/technical-hub)

## RESPONSIBLE PERSON

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Floorscape Cork is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of Floorscape Limited:



Mike Caird  
GENERAL MANAGER SALES & MARKETING  
23 November 2023