

PRODUCT NAME: FLOORSCAPE UNDERLAY

BPIR DECLARATION

Version: V1 December 2023

DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Floorscape (NZ) Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the [Building \(Building Product Information Requirements\) Regulations 2022](#)

COMPANY DETAILS

Manufacturer Legal and trading name / Address for service	Unilin Group, Ooigemstraat 3 8710, Wielsbeke, West-Flanders, Belgium
Manufacturer Website / Email	https://unilin.com/en aftersales@unilin.com
Importer legal and trading name / Address for service	Floorscape Limited, Unit 3 /19 Triton Drive Auckland 0632
Importer website / email	https://floorscape.co.nz/ sales@floorscape.co.nz
Importer NZBN	9429031816861
Importer phone number	094760428
Sustainability Information	https://unilin.com/en/one-home
Product Code Identifier	NZC-LAY / NZQSC-LAY / SENSU

DESCRIPTION OF BUILDING PRODUCT / INTENDED USE

Floorscape Underlay is used for floating floor installations. Floorscape have various types of underlay depending on size and foam density requirements. Floorscape underlay is a high quality closed cell physically cross-linked polyolefin foam which is 2mm in thickness. It includes a DPM (Damp Proof Membrane) and comes in roll format.

Further detail and technical information for Floorscape Underlay can be found at [Technical Data Sheets - Floorscape](#) (TDS Quiet-Step Underlay)

RELEVANT NEW ZEALAND BUILDING CODE CLAUSES

CLAUSE	EVIDENCE
G6 Airborne and impact sound — G6.3.1, G6.3.2	Floorscape Laminate has acoustic certification for standard ISO140-7 : Sound Transmission and Insulation standard (SPR test certification)

SCOPE OF USE AND LIMITATIONS

SCOPE	LIMITATION
Can be installed underneath floating flooring in all general interior areas of a building	<ul style="list-style-type: none"> - Remove all existing carpet or soft flooring and underlays - Not suitable for exterior use - All subfloors need to be sound and structurally stable enough to be installed atop. Any loose parts of the subfloor or hard flooring need to be secured, repaired, or removed and replaced. Subfloor must be flat with no unevenness greater than 2mm over the length of 1 metre in any direction. Clean and free of old adhesives, building rubble etc prior to installation. Concrete subfloors must test below 80%RH. Timber subfloors must test below 14%MC.

RESPONSIBLE PERSON

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Floorscape Underlay is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of Floorscape Limited:



Mike Caird
GENERAL MANAGER SALES & MARKETING
23 November 2023